

COPY

**METHODS AND APPARATUS FOR PROVIDING INFORMATION
IN RESPONSE TO TELEPHONIC REQUESTS**

Reference to Related Applications

This application claims priority of U.S. provisional patent application Serial Nos. 60/083,058, filed April 24, 1998, and 60/083,616, filed April 30, 1998. The contents of both of which are incorporated herein by reference in their entirety.

Field of the Invention

This invention relates generally to information distribution and, more particularly, to apparatus and methods for providing desired information to users of telecommunications devices such as cellular telephones.

Background of the Invention

With the wide proliferation of cordless and cellular telephones, it is increasingly common to have a phone in close proximity while listening to the radio in a car or watching television at home. There are currently over 66 million cellular telephone users in the United States, and this number is increasing rapidly. Cell phone users carry these devices wherever they go, particularly since newer services cover much a broader area, including the entire country in a growing number of situations.

09691912-062601

It would be advantageous, if not profitable, for advertisers and other information providers to interact with telephone users, particularly if it the interaction results in the sale of products or services in a given area. Ironically, even with the growing number of portable phones, it is difficult for consumers to respond to offers or receive more information from advertisers. One source of the difficulty is the large number of digits that must entered to contact the advertiser and identify the type of information desired.

Radio advertisers, in particular, now reach a greater number of individuals, in close proximity to a telephone due to the widespread use of mobile phones. Nevertheless, if the driver or passenger in an automobile must dial a seven-digit number followed by several other pushbutton entries to obtain certain information, many will either forget the number to call or lose interest. Even with automated voice-prompted menu selections, the caller might need to remain on the line longer than they wish to.

U.S. Patent No. 5, 703,795, which is incorporated herein by reference, discloses the derivation of station (S), date (D), time (T) and response (#) data to correlate a user's response to a particular piece of broadcast information (SDT). In each case, however, specified hardware is required for storing SDT# at a receiver site, and for communicating the data via the Internet or a point-of-sale (POS) system to a

00001912.062601
109290.276986

central location, where it is compared to broadcast station logs to convey an appropriate reply to the user. If an SDT-type protocol could take advantage of existing telecommunications devices, the resulting system might be more easily implemented since even fewer changes would be required to the existing infrastructure.

Summary of the Invention

The subject invention resides in methods and apparatus for providing a reply to a telephone caller, including inputs from the telephone caller which are in an abbreviated form. According to a method aspect of the invention, a message is received from a telephone caller during a telephone call, and supplemental information is derived which relates to at least one of the telephone caller and the telephone call. Using the message from the caller in combination with the supplemental information, an appropriate reply to the message is identified, which is then provided to the caller. The invention is applicable to various telecommunications infrastructures, including cellular telephony.

In a preferred embodiment, the message is a numerical or alphanumeric code entered by the caller using the telephone. The message may be provided by the caller, for example, in response to a request forming part of a radio or

television broadcast. In such a case, the message might relate to channel number or broadcast frequency, with the system storing a channel map to identify the station responsible for the broadcast, if so required. The
5 supplemental information relating to the caller would typically include at least a portion of the telephone number of the caller, or may additionally relate to the date or the time of the telephone call. Depending upon the circumstances, the date/time of the call may form part of the message.

10 The reply to the caller may occur during the telephone call, wherein the system might place an additional telephone call to identify the appropriate reply. Such a call may be toll-free, in which case the user may be patched-in to receive the information. Alternatively, the reply may be in
15 the form of a subsequent telephone call, a facsimile, or electronic mail later directed to the caller. As one example of many, digital music may be downloaded to a particular e-mail address as a reply to a telephonic request, with royalties or other charges being allocated in accordance with
20 pre-programmed criteria. In the case of an advertisement, the advertiser will additionally pay for the telephone charges, whereas, if the information itself has value, as with a copyrighted song or other information, the caller will typically be billed or debited, as appropriate.

25 Depending upon the physical implementation, voice

recognition apparatus may be used to interpret a message from the caller, and speech synthesis may be used to provide the reply. The invention is not limited to radio/TV broadcasts, in that the user may be responding to an outdoor advertisement
5 such as a billboard. In such an embodiment, a global positioning satellite system is preferably employed to derive the location of the caller to provide an appropriate reply in response to an incoming call. Other aspects of the invention are disclosed, including apparatus to carry out the various
10 methods.

Brief Description of the Drawings

FIGURE 1 illustrates a radio/cell phone environment according to the invention;

FIGURE 2 is a drawing of a car dashboard which
15 includes an integrated navigation and communication system applicable to certain embodiments of the invention;

FIGURE 3 depicts a billboard adapted for use with a GPS/mobile phone embodiment of the invention; and

FIGURE 4 is a drawing which shows how a user's
20 response may be used to disseminate a customized reply.

Detailed Description of the Invention

This invention improves upon the "PassKey" system disclosed in U.S. Patent No. 5,703,795, by applying the

derivation of station, date, time and response (SDT#) to users of standard, unmodified telephones and related equipment. Although the examples presented focus on the use of cellular telephones, the invention is applicable to other type of telecommunications devices such as personal digital assistants with cellular modems, as well as cordless and wired phones, depending upon the particular embodiment. Note also that references to the "telephone company" should be interpreted to include the existing and future-implemented public telephone network, as well as private telephone answering services, including those equipped to use the PassKey system as described previously or herein.

Broadly, according to the invention, when a telephone call is placed, existing telephone company technology is used where possible to derive supplemental information associated with the identity of the caller and nature of the interaction. Such supplemental information would ordinarily include one or more of the following:

- the caller's originating phone number,
- the caller's area or location (cellular zone for mobile phones or prefix area for fixed phones), and
- the date and time of the call.

The amount of supplemental information required to uniquely identify a caller and satisfy a particular request will increase with potential congestion due to the frequency

Alternatively, if advertisements are sufficiently spaced apart in time, the date may be sufficient without the exact time. In the general case, however, with potential responses being closely spaced in terms of frequency and geography, supplemental information relating to station, date, and time may be required along with additional information relating to the phone user to uniquely identify a particular broadcast, program offer, or other potential transaction.

When the call is received at the cell-phone company, the user's phone number, location, date and time of call, and the number 23 are recorded. In this example, the announcer could also request that the user indicate a response to a question as part of a contest, quiz, poll, and so on. If a

MRJ-10002/03
90804sh

multiple-choice question with three possible answers was announced, and the user's guess was 2, the user would key in *232. Once the call is received and the data logged in at the phone company, a beep tone would preferably be transmitted
5 back to the user, indicating that the entry has been acknowledged to the user can terminate the call.

As an alternate to the entry of an announced code, the station may be identified by broadcast frequency radio stations or the channel number for television and cable
10 broadcasts. Or the station call letters could be entered using the telephone keypad in the same way that names are now spelled for automated company directories. Thus, in the case of a car radio, the user could simply look at the radio display of frequency, and simply key it in, preceded by an
15 appropriate character such as the * key. Note that since FM stations in the U.S. are at odd frequencies and AM stations are at even frequencies, the system can differentiate between AM and FM stations just by analyzing the frequency. As examples, *1051 would be interpreted to mean FM station at
20 105.1 MHZ FM, whereas *1070 would mean 1070 KHz AM.

For cable system users it might be convenient to store, at a central location accessible by the phone company, the channel maps for the various cable companies, so that the actual station can be determined from its channel number in
25 that cable system. A table would also preferably be stored

00001912-062601
109290-2T6T6860

identifying the various cable companies in each telephone system zone. In situations where there are multiple cable/DSS/microwave TV providers in a particular zone, the user may be required to call the phone company in advance and register
5 his cable company with his phone number to take full advantage of the invention. Such registration would preferably be carried out in an automated, voice-actuated manner.

In a comprehensive embodiment of the invention, the phone company will be able to record SDT# as well as user ID
10 in response to an incoming call. In the case of a broadcast ad, "T" may be delayed from the time of the broadcast due to delays in the phone system or delays by the caller in responding to the ad. This may not be a problem with emerging cellular phone, since newer digital units include a clock/
15 calendar function to display date/time. It is envisioned that these digital phones will also be programmed to store the date/time in the phone when a particular data string is entered, so that when the SEND button is pressed, the stored date and time is sent along with the station and pod number.
20 This, in turn, may be stored at the phone company for comparison with the program logs.

The problem of multiple advertisements broadcast in a closely spaced pod may alternatively be handled as follows:
If, for example, four different ads were broadcast one after
25 the other, the announcer would simply indicate "to respond to

109290 216162601

this ad enter *234 on your cell phone and press SEND now," if the particular ad was the fourth aired in the pod. In this instance it is important to distinguish whether the third digit being sent is to identify the pod number or the user's response. This can be handled in several ways: one way is to always announce a three digit ad identifier, even if the ad is the only one in the pod. Thus, the fourth digit and beyond will always be the user's response (in the example above, the user would key in *2342). Alternatively, the ad identifier digits could be separated from the user's response with a special symbol, such as *234*2, where 234 is the ad identifier and 2 is the user's response.

Once the phone company or other agency has received the information, the first two digits may be used to identify the relevant broadcast station, and in combination with the date, time and pod number, compared to the station log of that station to uniquely determine the information being responded to. The subsequent digits, if any, are the user's response which can be compared to the requested information, and a reply is generated. The reply can be communicated back to the user in print form on his/her cellular phone bill (a coupon, a winner notice, etc.). Alternatively, by registering a fax number, e-mail address or pager number, these and any other suitable means of communication back to the caller may be used.

Once a comparison is made, a broadcaster/advertiser
0 reply in the form of one of a series of pre-recorded messages
may be transmitted back to the user's phone while the caller
is still on the line (in this case, the confirmation beep tone
to hang up would not be transmitted). For example, if the
user guessed a contest question correctly, the message could
15 say "you have won, and your prize is waiting for you at your
local Sears store," or "sorry, your answer is incorrect," and
so on, depending upon the outcome of the comparison of the
user's response to the winning data stored in conjunction with
the program log. In the event that the user has won a money
20 prize, it could automatically credited on his cell phone bill
(the phone company would recoup this amount plus a service
charge from the advertiser/broadcaster).

11

Alternatively, in an off-line callback embodiment, since the phone company stores the originating phone number, the user can hang up, the comparison with the station log can be performed at a later time, and a call from the advertiser to the user can be made at a later time. A recorded announcement would preferably be made to the user during the originating call to alert the user to expect a callback. Only five key strokes (*2342) would be necessary to make this call, which is much more convenient and memorable than an 11-digit phone number. As users become familiar with the initial entry of the * symbol, only 4 numbers would need to be remembered.

12

frequency. When a connection is made, a voice will request the user to either dial or SAY the user's response (and/or pod number) or any other information requested by the advertiser. Thus, the maximum keypad entries for any ad, including a pod
5 number and a user response, would be five (*FREQ). By using voice recognition, a user response could be a word, such as YES or NO, as opposed to a number.

In yet another embodiment, the use of the * or # key can be eliminated. For example, assume that all responses are
10 to be directed to a toll-free number such as 1-800-555-1234. Most cell phone include a store and recall function where the user can store frequently used numbers in various recall (RCL) positions (usually designated by a number from 1-99). If the user stores the toll-free number in position 3, when the user
15 hears/sees an ad of interest, he or she simply enters RCL3 and SND. When connected, voice responses (and optionally voice recognition) software is used to prompt the user to enter or SAY the station frequency, pod number and/or response.

Thus, in this embodiment, it is possible to reduce
20 the keypad entries to just two (RCL(x)), whereby SDT# are all stored at the receiving location. Moreover, although this example uses a cell phone/car radio combination, it will be appreciated that the same system is equally applicable to a TV or radio broadcast in conjunction with a cordless/cord phone
25 example for home use.

5

15

25

or caller, including, for example, geographical area (through area code or cell prefix), as well as the name, address, and other phone/fax numbers, e-mail address, and so forth. Such supplemental may have either been provided by the caller when
5 signing up for the service, or the system may refer to other databases 123 which may include on-line directories to gather additional supplemental information.

In addition to the supplemental information being gathered about the caller, the "94" content of the
10 transmission is used in conjunction with the date and/or time of day to determine the offer which the user is responding to. In this case, from database 124, it is determined that at 4:05, the station broadcasting on frequency 93.9 did, indeed, send out an offer regarding "West Coast Technical." Note that
15 although databases 120 and 124 are shown as separate, they may co-located or distributed, with the any form of public or private communications network being used to integrate the data. Nor do the database look-ups need to be sequential, since the incoming call may trigger simultaneous inquiries to
20 determine supplemental information about the call and the caller at the same time to avoid delays.

Having determined additional information about the caller and the nature of the broadcast, the system has what it need to formulate a reply 130 to the user/caller. As
25 discussed elsewhere herein, this replay can come in various

forms, which need not be mutually exclusive. In general, the
reply is limited only to the extent of the information in the
databases. That is, if the database 120 includes an address,
the information can be mailed. If other phone or FAX numbers
5 are present, they can be used as well. If an e-mail address
is stored or entered by the caller, desired information may be
downloaded to that address. If the advertiser includes a
method of contact such as an 800 number 128, the user/caller
may be patched into the advertiser as discussed elsewhere
10 herein.

Given this wide range of responses, according to a
best mode of carrying out the invention, it is expected that
upon receipt of a call from a caller, the system will perform
a search to determine whether that caller has previously
15 registered a mailing address, FAX number, and so forth.
Having determined this information, the system will preferably
lead the caller through a series of automated options, perhaps
using the caller's name in synthesized form, as follows:

"Hello June Williams. Thanks for your interest in
20 West Coast Technical.

If you would like to receive further information by
mail, press or say "1."

For further information by FAX, press or say "2."

To have the information sent to your e-mail address,
25 press or say "3."

If you would like to have a West Coast Technical representative call you later at home, press or say "4."

If you would like to have a West Coast Technical representative call you later at work, press or say "5."

5 To speak directly with a West Coast Technical representative, just stay on the line."

Thus, in the above example, a search with respect to the caller would have determined that June Williams had provided a mailing address, a FAX number, an e-mail address, and home/work telephone numbers, such that all of the options would be appropriate. Also, in the case of an advertisement, the advertiser will preferably pay for the call from the caller (in addition to the ad), allowing the broadcaster to inform potential callers that their call will be free, thereby soliciting the largest audience. The ability to segregate incoming calls for such specialized payments may be accomplished through particularized encoding in an external or outlying billing system or revenue charging system 128 associated with call rating/billing. Note that as another advantage of the invention, due to the integration of caller background and demographic data, potential advertisers may be provided with access to customer credit history and other financial information, thereby gaining an insight into their level of qualification.

25 Note that the information need not be textual or

graphical, but may also include audio and/or video information. For example, a radio station may provide a service whereby a caller may enter the station frequency (or other alpha/numeric identifiers) during a song, in which case
5 the song will automatically be downloaded in digital form to the caller's e-mail address, enabling the caller to record the song on a digital music player of the type now offered by Rio Corp. Such a system according to the invention would not only be convenient, it would allow the agencies responsible for the
10 collection of royalties to charge the caller for the download and distribute the payments as appropriate under copyright law, which is currently being circumvented in many cases.

In addition to broadcast ads, automobile occupants in particular are also subjected to a variety of other media
15 such as outdoor billboards. Many of these list a phone number to contact the advertiser of other information provider. As with radio ads, however, this form of communication is not very effective, since the user is often not in a position to remember a long phone number or to write it down. The
20 embodiments of the invention described below overcome this shortcoming by providing a simple and automatic way for a user to respond to non-broadcast advertising and other applicable media, and to receive a reply to that response.

Many new car models are being equipped with digital
25 navigation systems based upon the global positioning satellite

(GPS) system for position information. The navigation system is capable of identifying the car's location to within a few feet, and can also determine the direction of travel. Referring to Figure 2, there is shown a car dashboard 10 which includes a navigation system and display 12 and a mobile cellular phone 14. It is envisioned that the phone 14 would be connected to communicate with the navigation system 12 whenever a particular key sequence is entered on the phone keypad. For example, the sequence #-3 could be used to enable this feature. Once this sequence is entered, the phone 14 receives from the system 12 information indicating the location of the car. The location might be in the form of latitude and longitude coordinates, as shown in the following table:

Latitude	Longitude	Billboard ID#	Phone #	Reply
37.845N	118.254W	2	1-213-555-6740	Budget Auto Rental Auto Dial phone # and connect
34.627N	76.923W	6	1-818-555-1273	Danny's Restaurant 1=brunch 2=lunch 3=dinner Send coupon with phone Bill

Referring to Figure 3, there is shown a billboard configured to be used with this embodiment of the invention.

10 When a user drives by a billboard and wants to respond to the ad, the user simply enters the key sequence (#3) followed by the billboard identifier (2 in the case of Figure 2). The user can also follow this with a numerical response, if prompted for one by the ad. For example, in
15 Figure 3, the user would just enter #32, and in the case of Figure 4, might enter #362 to receive a lunch coupon. In each case, the key sequence is followed by the SEND key. When these key sequences are entered, the phone 14 receives the car location coordinates from the system 12, and transmits that
20 along with the key sequence to the phone company. At a location accessible to the phone company, a billboard database is stored which contains the coordinates of the participating billboards, along with their ID numbers, and any reply information such as phone numbers, answers to questions, etc.
25 Table 1 shows an example of such a database for the billboards

of Figures 2 and 3.

09891912 "062601

The received data from the user is compared to the database to find the billboard in question using the coordinates and ID number, and the appropriate reply is
5 communicated back to the user. In the case of Figure 3, the phone company preferably autodials the auto rental phone number and connects the user directly to the advertiser. This may be in real time, or might be in the form of a call back, as described above. In the case of Figure 4, the user's
10 response (2) is noted and the user is preferably sent a lunch coupon from Danny's Restaurant in a subsequent cell-phone bill.

Due to errors in the navigation system and variations with respect to the time at which the user sends
15 the information to the phone company, it is envisioned that a "guard band" of coordinates would be established for each billboard to ensure that it is correctly identified over a range of coordinates. The billboard ID numbers would be assigned to ensure that all billboards falling within that
20 guard band could be uniquely identified.

Note that by using voice recognition software at the receiving end, the need for a GPS system can be eliminated. For example, using the RCL function described above, the user would dial the PassKey 800 number, and is asked to enter
25 location and billboard number. For example, assume a Budget

MRJ-10002/03
90804sh

Auto Rental billboard number 2 was seen at the corner of Wilshire Boulevard and Rodeo Drive in Beverly Hills. In response to the question "Where are you?", the user would respond with that location, and in response to "What billboard
5 are you interested in?" The user would respond with the billboard number. Alternatively, the user could also say the name of the billboard advertiser, such as Budget." In this embodiment, numbering of the billboards would not be necessary.

10

I claim: